23MY ISUZU D-MAX SPECIFICATIONS

Engine	3.0L	1.9L
Series	Isuzu 4JJ3-TCX	RZ4E-TC
Description	3-litre turbo-diesel, in-line 4-cylinder, DOHC, 16-valve with Diesel Particulate Diffuser (DPD)	1.9-litre turbo-diesel, in-line 4-cylinder, DOHC, 16-valve with Diesel Particulate Diffuser (DPD)
Maximum torque	450Nm @ 1600→2600 rpm (automatic & manual)	350Nm @ 1800 \rightarrow 2600 rpm (automatic and manual)
Maximum power	140kW @ 3600 rpm	110kW @ 3600 rpm
Bore x stroke	95.4mm x 104.9mm	80mm x 94.4mm
Displacement	2999cc	1898cc
Compression ratio	16.3:1	15.9: 1
Cylinder head	Isuzu-patent special aluminium alloy	Isuzu-patent special aluminium alloy
Valve gear	Chain-driven dual overhead camshafts, roller rockers, 4 valves/cylinder	Chain-driven dual overhead camshafts, roller rockers, 4 valves/cylinder
Induction	Electronic high pressure common rail direct fuel injection with VSS (Variable Swirl System) and intercooled electric control VGS (Variable Geometry System) turbocharger	Electronic high pressure common rail direct fuel injection with VSS (Variable Swirl System) and intercooled electric control VGS (Variable Geometry System) turbocharger
Cylinder block	Cast iron upper with induction-hardened cylinder bores, cast alloy lower	Cast iron upper with induction-hardened cylinder bores, cast alloy lower
Emission level	Euro 5	Euro 5
Alternator	90 amp with Intelligent Battery Sensor (IBS)	90 amp with Intelligent Battery Sensor (IBS)

Transmissions

Manual	275mm diameter 1.9L Engine: Isuzu	3.0L Engine: Isuzu MVL-6S 6-speed manual with high torque capacity and output reduction, 275mm diameter clutch plate and dual mass flywheel 1.9L Engine: Isuzu MVL-6Y 6-speed manual with high torque capacity and output reduction, 275mm diameter clutch plate and single mass flywheel													
Automatic	with fuel-saving lo ▶Uphill/Downhill 7	Aisin AWR6B45 II 6-speed with sequential shift and brake shift lock electronically controlled, tri-mode with fuel-saving lock-up torque converter on gears 3, 4, 5 and 6 ▶ Uphill/Downhill Transmission Control: holds gear in varied-gradient ascents, selects gear on steep descents to hold speed with engine braking													
Ratios: 1	3.0L Turbo 1st 2nd 3rd 4th 5th 6th Reverse	6-speed Manual 4.942 2.452 1.428 1.000 0.749 0.634 4.597	6-speed Automatic 3.600 2.090 1.488 1.000 0.687 0.580 3.732	1.9L Turbo 1st 2nd 3rd 4th 5th 6th Reverse	6-speed Manual 4.942 2.686 1.527 1.000 0.749 0.634 4.597	6-speed Automatic 3.600 2.090 1.488 1.000 0.687 0.580 3.732									
Final drive	4x2 4x4 Snorkelled diff bre	3.727 3.727	3.727 3.727	4x2	4.100 -	4.100									
Transfer gearing	4x4 low-range 4x4 high-range	2.482 1.000	2.482 1.000	ia reduce mad bio	ckage										
4x4 system	"Terrain Comman rear differential loc		shift on the fly' 2-l	nigh≪→4-high sele	ection at up to 100	cm/h, 4-low with									
Drivetrain system	TCS (Traction Con	trol System) on	all model variants												

Steering

Electric power steering with speed-sensing steering feel (light at low speed, heavy at high speed); tilt and telescopic adjustable steering wheel

Engine-speed-sensitive variable capacity Electric power system; 3.84 turns lock-to-lock via tilt-adjustable steering wheel

Chassis

Separate, full-length heavy-duty chassis with 8 cross members on all models

Front suspension

Independent, high-ride, coil springs, gas shock absorbers, upper and lower wishbones, stabiliser bar

Rear suspension

LS-M and all Cab Chassis models: Heavy Duty alloy-steel overslung long-span semi-elliptic leaf springs; gas shock absorbers

4x2 and 4x4 models: Alloy-steel overslung long-span semi-elliptic leaf springs; gas shock absorbers

Axles

Front

Independent 4x4: fully floating with outer CV, inner double offset joints and equal length driveshafts. Rating: 1450kg

Rear

Rigid semi-floating banjo with hypoid final drive and dual tapered needle roller bearings. Rating: 1910kg

Brakes

Anti-lock Brake System (ABS) with Electronic Brakeforce Distribution (EBD), Electronic Stability Control (ESC), Emergency Brake Assist (EBA), Traction Control System (TCS), Rollover Mitigation, Hill Start Assist (HSA), Hill Descent Control (HDC) and Trailer Sway Control (TSC)

320mm dia. ventilated front discs with 2-piston calipers. 295mm rear drums

Power-assisted via 10" servo unit; central pull up park brake

Wheels and Tyres

SX	17" x 7" drilled Silver-Finish Steel; 255 / 65 R17 All-Terrain
LS-M	17" x 7" alloy; 255 / 65 R17 All-Terrain
LS-U and LS-U+	18" x 7.5" alloy; 265 / 60 R18 Highway-Terrain
X-TERRAIN	18" x 7.5" matte Dark Grey Alloy; 265 / 60 R18 Highway-Terrain
All Models	Full size steel spare wheel

Service Plus

Warranty	For the ultimate peace of mind, every Isuzu D-MAX comes standard with a comprehensive, bumper-to-bumper 6 years/150,000km warranty^.
Roadside Assistance	Enjoy up to 7 years Roadside Assistance ^{<} when you complete your scheduled services at a Participating Isuzu UTE Dealer.
Capped Price Servicing	As an owner you will get access to our Capped Price Servicing Program. The CPS Program covers the first 7 Scheduled Services in line with the Scheduled Service Intervals.

^6 years/150,000km (whichever occurs first), for Isuzu UTE Vehicles with a Warranty Start Date on or after 1/1/19. Excludes trays & accessories. 'The Roadside Assistance Program ("RSA Program") provides Coverage to RSA Eligible Vehicles (Private, ABN and Business Fleet Customers only) with a Warranty Start Date on or after 1/9/20 for a maximum of 7 years (unlimited kilometres). Initial 13 months Coverage provided from the Warranty Start Date. The Coverage will be reset for another 13 months from each date that a Participating Isuzu UTE Dealer conducts a Scheduled Service on the vehicle. For full terms & conditions visit isuzuute.com.au/ roadside-assistance-disclaimer. >The Capped Price Servicing Program ("CPS Program") applies to CPS Eligible Vehicles (excludes Rental & Government Customers) at Participating Isuzu UTE Dealers only. For 19MY & later vehicle models, the Capped Price Servicing covers the first 7 Scheduled Services for up to 7 years/105,000km (whichever occurs first). CPS Program is subject to change. For full terms & conditions, current pricing & model eligibility visit isuzuute.com.au/ service-plus-disclaimer.

Safety

IDAS	Every D-MAX comes with Isuzu's
	Intelligent Driver Assistance System
	(IDAS#) built-in to protect and enhance
	the driving experience. IDAS includes
	smart technologies as well as other
	passive and active safety features.

*IDAS features are designed to assist the driver, but should not be relied upon nor used as a substitute for safe driving practices. Feature operation may vary in different driving conditions. For full explanation of limitations, see Owner's & Driver's Manual.

	ANCAP RATING	The entire D-MAX range has achieved a maximum 5-star ANCAP safety rating in 2020.
--	-----------------	---

SPECIFICATIONS		4x2	High-R	Ride⁺		4x4+											
	Single Cab Chassis	Space Cab Chassis	Crew Cab Chassis	Crew Cab Ute	Crew Cab Ute	Single Cab Chassis	Space Cab Chassis	Space Cab Ute	Crew Cab Chassis	Crew Cab Ute	Crew Cab Chassis	Crew Cab Ute	Crew Cab Chassis	Crew Cab Ute	Crew Cab Ute	Crew Cab Ute	
	SX	SX	SX	SX	LS-U	SX	SX	LS-U	SX	SX	LS-M	LS-M	LS-U	LS-U		X-TERRAI	
Engine																	
1898cc DOHC 4cyl. with intercooled turbocharger (350Nm, 110kW) 2999cc DOHC 4cyl. with intercooled turbocharger (450Nm, 140kW)		•			•	•	•	•	•		•	•	•	•	•	•	
Transmissions																	
6-speed manual transmission	•					•			•								
6-speed "Rev-Tronic" automatic transmission with sequential sport mode	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Safety and Security																	
4-channel 4-sensor Anti-lock Brake System (ABS) with Electronic Brakeforce Distribution (EBD)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Electronic Stability Control (ESC)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Traction Control System (TCS)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Emergency Brake Assist (EBA)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Hill Start Assist (HSA)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Hill Descent Control (HDC)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Autonomous Emergency Braking (AEB)		•	•	•		•	•	•	•		•			•		•	
Turn Assist with AEB Post-Collision Braking																	
Forward Collision Warning (FCW)																	
Misacceleration Mitigation (*AT models only)	•*					*	•		*								
Adaptive Cruise Control (ACC) with Stop and Go functionality (*AT models only)	•*	•	•	•	•	•*	•	•	•*	•	•			•		•	
Traffic Sign Recognition (TSR)	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	
Intelligent Speed Limiter	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Manual Speed Limiter	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Lane Departure Warning (LDW)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Lane Departure Prevention (LDP)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Lane Keep Assist (LKA) (*AT models only)	•*	•	•	•	•	•*	•	•	•*	•	•	•	•	•	•	•	
Emergency Lane Keeping (ELK)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Lane Support System (LSS) Switch (disables LDW, LDP, LKA, ELK)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Driver Attention Assist Blind Spot Monitoring (BSM)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Rear Cross Traffic Alert (RCTA)											•						
BSM/RCTA Auto Switch Off (disables BSM/RCTA when the genuine tow harness is connected)																	
Reversing camera					•					•							
Rear Park Assist Sensors					•			•						•	•	•	
Front Park Assist Sensors																•	
8 Airbags: dual front, curtain, side, driver's knee and far side airbags	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Passenger side SRS airbag on/off switch	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Height-adjustable upper mounts for front seat belts	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Pre-tensioners with load limiters for front seat belts	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Pre-tensioners with load limiters for outer rear seat belts			•	•	•				•	•	•	•	•	•	•	•	
3-point retractable seat belts for all rear and centre seating positions		_	•	•	•	_	_		•	•	•	•	•	•	•	•	
Intelligent seatbelt reminder (all seats) 2 childseat tethers and ISO FIX compatible anchor points	•	•				•	•	•									
2 childseat tethers and ISO FIX compatible anchor points Height-adjustable head restraints for full-size seats																	
Integrated head restraints for full-size seats			•	•	•		•	•		•					•		
Child-proof rear door locks			•	•	•				•	•	•	•	•	•	•	•	
Single 10 inch servo brake master cylinder	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Side anti-intrusion bars inside all doors	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Engine immobilizer	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Rear window demister		•	•	•	•		•	•	•	•	•	•	•	•	•	•	
High Density Polyethylene (HDPE) fuel tank	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
High mount brake light on cabin	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Dual horn	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Protection																	
Under-front steel skid plate	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Steel plate guards: sump, transfer case, fuel tank leading edge; reinforced resin under fuel tank						•	•	•	•	•	•	•	•	•	•	•	
Suspension and Brakes																	
Standard rear leaf suspension				•	•			•		•				•	•	•	
Heavy duty rear leaf suspension	•	•	•			•	•		•		•	•	•				
Front independent, coil spring suspension w/gas shock absorbers, upper and lower wishbones and stabiliser bar	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Heavy-duty brakes: 320mm ventilated front discs w/twin-pot calipers, 295mm rear drums	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	

^{*}Limited stock available on these models. Please contact your local Isuzu UTE Dealer for more information.

CDECIFIC ATIONS

SPECIFICATIONS		4x2	? High-Ride⁺								4x4+					
	Single Cab	Space Cab	Crew Cab	Crew	Crew	Single Cab	Space Cab	C	C Cab	Crew	Crew Cab	Crew	Crew			
	Chassis SX	Chassis SX	Chassis SX	Cab Ute	Cab Ute	Chassis SX	Chassis SX	Cab Ute	Crew Cab Chassis SX	Cab Ute	Chassis LS-M	Crew Cab Ute LS-M	Cab Chassis LS-U	Crew Cab Ute LS-U	Cab Ute	
In-cabin Storage																
Lower glovebox compartment only	•	•	•	•		•	•		•	•						
Upper and lower glovebox compartments					•			•			•	•	•	•	•	•
Power outlet in lower instrument panel	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Centre floor console	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Dual-purpose driver and front passenger cup holder tray	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Rear passenger door cup holders			•	•	•				•	•	•	•	•	•	•	•
Pockets on backs of front seats					•			•			•	•	•	•	•	•
Overhead console with twin map lights and flip-down sunglasses case	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Front door storage compartment with bottle bulge	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
2 coat hooks			•	•	•				•	•	•	•	•	•	•	•
Flip up convenience hook behind passenger front seat								•								
Tool storage behind rear seats		•	•	•			•		•	•	•	•		•		•
Tool storage behind front seats						•								•		
						•										
Rear Tub																
Double-walled ute tub				•	•			•		•		•		•	•	•
4 cargo tie-down hooks inside ute tub				•	•			•		•		•		•	•	
Under rail tub liner					•			•						•	•	•
2 cargo tie-down hooks inside ute tub																•
Tailgate Assist				•	•			•		•		•		•	•	•
Exterior Style																
Short front overhang for optimal manoeuvrability and approach angle					•								•			•
Halogen multi-reflector project lens headlights for extra low beam depth and reduced flare								•			•		•			•
	_	•	•	•		•	•		•	•						
Bi-LED headlights with auto-levelling function		_		_	•		_	•	_		•	•	•	•		•
Automatic headlights		•	•	•	•		•	•	•	•	•	•	•	•		•
Automatic high beam		•	•	•	•		•	•	•	•		•	•	•	•	•
Coming home light	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Welcome light					•			•					•	•	•	•
LED Daytime Running Lights (DRLs)					•			•			•	•	•	•	•	•
LED fog lights					•			•			•	•	•	•	•	•
Black radiator grille	•	•	•	•		•	•		•	•						
Black-Grey radiator grille											•	•				
Chrome radiator grille					•			•					•	•	•	
Dark Grey radiator grille																•
Colour-coded front bumper	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Colour-coded integrated rear step bumper				•	•			•		•		•		•	•	•
Black rear bumper	•	•	•			•	•		•		•		•			
Factory fitted tow bar receiver					•			•					•	•	•	•
Space cab rear "wing" doors		•					•	•								
Aluminium side steps					•			•					•	•	•	
Dark Grey side steps																•
Black door and tailgate handles	•	•	•	•		•	•		•	•						
Colour-coded door and tailgate handles											•	•				
Chrome door and tailgate handles					•			•					•	•	•	
Dark Grey door and tailgate handles																•
Lockable tailgate				•	•			•		•		•		•	•	•
Dark Grey Aero Sports Bar																•
Matte Black roller tonneau																•
Dark Grey front and rear underbody spoilers																•
Dark Grey finder flares																
Dark Grey roof rails																
Black power door mirrors			_	_												
Colour-coded power door mirrors with integrated turn indicators		•	•	•		•				•	_	_				
					•						•	•				
Chrome fold-in power door mirrors with integrated turn indicators					•			•					•	•	•	_
Dark Grey fold-in power door mirrors with integrated turn indicators													_	_		•
Heated door mirrors					•	_		•					•	•	•	•
Centre front roof-mounted bee-sting aerial	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
LED rear combination lamps					•			•						•	•	•

^{*}Limited stock available on these models. Please contact your local Isuzu UTE Dealer for more information.

SPECIFICATIONS		4x2	2 High-F	Ride⁺		4x4+											
SPECIFICALIUMS																	
	Single Cab Chassis	Space Cab Chassis SX	Crew Cab Chassis SX	Crew Cab Ute SX	Crew Cab Ute LS-U	Single Cab Chassis	Space Cab Chassis SX	Space Cab Ute LS-U	Crew Cab Chassis SX	Crew Cab Ute	Crew Cab Chassis LS-M	Crew Cab Ute LS-M	Crew Cab Chassis LS-U	Crew Cab Ute LS-U	Crew Cab Ute	Crew Cab Ute X-TERRAIN	
Seating	SX	SX	SX	SX	LS-U	SX	SX	LS-U	SX	SX	LS-IVI	LS-IVI	LS-U	LS-U	LS-U+	X-TERRAIN	
Standard Black cloth seats	•	•	•	•		•	•		•	•							
High Grade cloth seats					•			•			•	•	•	•			
Leather Accented seats															•		
Leather Accented seats with Red Stitching																•	
Front bucket whiplash protection seats	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
6-way adjustable driver seat	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
8-way electric adjustable driver seat															•	•	
Electric adjustable lumbar support (driver seat only)					•			•					•	•	•	•	
Heated front seats															•	•	
Split-fold rear seat			•	•					•	•							
Split-fold rear seat with centre arm rest					•						•	•	•	•	•	•	
Rear centre seat headrest			•	•	•				•	•	•	•	•	•	•	•	
Cabin Amenities																	
Dual zone climate control air-conditioning with integrated heater/demister																	
Manual air-conditioning with integrated heater/demister					•			•					•				
Rear seat air-conditioning vents		•					•										
Pollen and fine particle air filter							•										
Power windows with one-touch up/down driver's window with safety stop and delay closing																	
Comfort turn signal																	
Central locking with keyless entry																	
Smart keyless entry		_	•				•		•		•	•					
Walk away lock																	
Push button start																	
Remote engine start																	
Power-adjustable door mirrors with turn indicator lights					•			•			•	•	•	•	•		
Power-adjustable door mirrors	•	•	•	•		•	•		•	•							
4 speaker sound system																	
6 speaker sound system			•	•			•	•	•	•	•	•					
"Sky Sound" roof-mounted sound system with 8 speakers (mounted in front dash, front doors, rear doors and roof)					•								•	•	•	•	
9 inch touchscreen display with Apple CarPlay® and Android Auto™								•					•				
7 inch touchscreen display with Apple CarPlay® and Android Auto™	•	•	•	•		•	•		•	•	•	•					
Built-in satellite navigation with MID turn-by-turn directions					•			•					•	•	•	•	
Rear centre console USB charging port			•	•	•				•	•	•	•	•	•	•	•	
Tilt and telescopic adjustable steering wheel with electric power steering	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Urethane steering wheel with cruise, audio and voice recognition controls	•	•	•	•		•	•		•	•	•	•					
Leather steering wheel with cruise, audio and voice recognition controls					•			•					•	•	•	•	
Smart MID with digital speedometer, safety information, fuel economy and range, odometer, trip information and service reminder	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Tyre Pressure Monitoring System (TPMS)					•			•					•	•	•	•	
Electro-luminescent gauges	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
"Terrain Command" 4x4 select dial						•	•	•	•	•	•	•	•	•	•	•	
Rear differential lock button						•	•	•	•	•	•	•	•	•	•	•	
Automatic windshield wipers	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Intuitive flat wiper blade					•			•					•	•	•	•	
Day/night interior rear view mirror	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Auto-dimming rear view mirror					•			•					•	•	•	•	
Sun visors with vanity mirrors (driver and passenger) and ticket retaining strap (driver)					•			•					•	•			
Sun visors with illuminated vanity mirrors (driver and passenger) and ticket retaining strap (driver)															•	•	
Fixed A-pillar assist-grips for driver and front passenger	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Fixed B-pillar assist-grips for rear passengers			•	•	•				•	•	•	•	•	•	•	•	
Folding assist-grips for driver and front passenger			•	•	•				•	•	•	•	•	•	•	•	
Folding assist grips for year passongers																	

Folding assist-grips for rear passengers

Carpet flooring
Easy-clean vinyl flooring

FUEL, WEIGHTS			42	κ2 Higl	n-Ride†				4x4+													
& DIMENSIONS	Cab Chassis C SX		Space Cab Chassis SX	Čab Cab Chassis Chassis SX SX		Crew is Cab Ute SX		Crew Cab Ute LS-U	Single Cab Chassis SX	Space Cab Chassis SX	Space Cab Ute LS-U	Crew Cab Chassis SX	Cak	rew o Ute SX	Crew Cab Chassis LS-M	Crew Cab Ute LS-M	Crew Cab Chassis LS-U	Crew Cab Ute LS-U	Crew Cab Ute LS-U+	Crew Cab Ute X-TERRAIN		
D-MAX ADR 81/02 ^a Fuel Consumption Values	1.9L	3.0L		1.9L			3.0L		A 4 7 / A 7			N 4T / AT	1.9L	3.0L						A.T.		
Transmission (MT = Manual, AT = Automatic)	MT/AT	MT/AT	AT	AT	AT AT		AT	AT	MT / AT	AT	AT	MT / AT	AT	AT	AT	AT	AT	AT	AT	AT		
FUEL CONSUMPTION (litres/100km) Combined	7.0	8.0	8.0	7.0	70 00		7.7	8.0	8.0	8.0	8.0	8.0	6.9	8.0	8.0	8.0	8.0	8.0	8.0	8.0		
Urban	8.1/7.9	10.2/9.8	9.8	7.0	7.0 8.0 7.9 9.8		9.5	9.8	10.2/9.8	9.8	9.8	10.2/9.8	8.1	9.8	9.8	9.8	9.8	9.8	9.8	9.8		
Extra Urban	6.5/6.6	6.7/6.9	6.9	6.6	6.9	8.3 6.0	6.7	6.9	6.7/6.9	6.9	6.9	6.7/6.9	6.3	6.9	6.9	6.9	6.9	6.9	6.9	6.9		
CO ² (g/km)	0.5/0.0	0.7/0.5	0.5	0.0	0.5	0.0	0.7	0.5	0.7/0.5	0.5	0.5	0.7/0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5		
Combined	183/184	206/207	207	184	207	177	200	207	206/207	207	207	206/207	180	207	207	207	207	207	207	207		
Urban	212/208	262/254	254	208	254	218	246	254	262/254	254	254	262/254	212	254	254	254	254	254	254	254		
Extra Urban	170/174	174/180	180	174	180	158	174	180	174/180	180	180	174/180	165	180	180	180	180	180	180	180		
Dimensions (mm unless stated otherwise)	170/171	17 17 100	100	.,.	100	100	.,,	100	17 17 100	.00	100	17 1, 100	.00	100	100	100	100	100	100	100		
	21	٥٢	2125	21	25	21	2125		0105	2125	2125	2125	2.	125	3125	2125	2125	2125	0105	2125		
Wheelbase Overall length	31 53		3125 5290		25 290		3125		3125 5330	3125 5290	3125 5275	3125			5290	3125 5270	3125 5290	3125 5275	3125 5275	3125 5303		
Overall width (excluding door mirrors)	18		1870		370	5270 1870		5275 1870	1870	1870	1870				1870	1870	1870	1870	1870	1880		
Overall height (*depends on body fitted)	17		1800*	18				1790	1790*	1800*	1790	1800*	1870 1870		1800*	1785	1805*	1790	1790	1810		
Front overhang		90	890		90	1785 890		890	890	890	890	890	1785 890		890	890	890	890	890	905		
Rear overhang (*depends on body fitted)	13		1270*	12		1250		1250	1310*	1270*	1250	1270*		250	1270*	1250	1270*	1250	1250	1250		
Wheel track width	15		1570		70	1570		1570	1570	1570	1570	1570	1570		1570	1570	1570	1570	1570	1570		
Ground clearance		35	235		35	235		240	235	235	240	235	235		235	235	240	240	240	240		
Turning circle diameter between kerbs (metres)		2.5	12.5		2.5	12.5		12.5	12.5	12.5	12.5	12.5	12.5		12.5	12.5	12.5	12.5	12.5	12.5		
Approach angle	29		29.6°	3		30°		30.5°	29.6°	29.6°	30.5°	29.6°		30°	29.6°	30°	30°	30.5°	30.5°	30.5°		
Departure angle	24		25.3°		i.3°	23.9°		19.0°	24.6°	25.3°	19.0°	25.3°		3.9°	25.3°	23.9°	20.6°	19.0°	19.0°	19.0°		
Ramp-over angle	23		23.9°		.9°	23.3°		23.8°	23.9°	23.9°	23.8°	23.9°		3.3°	23.3°	23.3°	24.3°	23.8°	23.8°	23.8°		
Load area (mm)																						
Cab to rear axle	12	40	765	1	450		450		450		1240	765	765	450	1	150	450	450	450	450	450	450
Length (top)	12	-	703		-	450 1495		450 1495	-	700	1805	-		495	430	1495	-	1495	1495	1495		
Length (floor) (*inside genuine accessory tray body)	25!	50*	2100*	18	_ nn*	1570		1570	2550*	2100*	1835	1800*		570	1800*	1570	1800*	1570	1570	1570		
Maximum width (*inside genuine accessory alloy tray body)	177		1777*	17		1530		1530	1777*	1777*	1530	1777*		530	1777*	1530	1777*	1530	1530	1530		
Width between wheel houses	17.	-	-		-		22	1122	-	-	1122	-		122	-	1122	-	1122	1122	1122		
Depth			-		-	4		490	-	_	490			90	-	490	_	490	490	490		
Interior (mm)							50	100			100					100		100	100	100		
Leg room - front	10	75	1075	10)75	10	175	1075	1075	1075	1075	1075	10	075	1075	1075	1075	1075	1075	1075		
	10	75	1075		05	9		905	1075	1075	1075	905		905	905	905	905	905	905	905		
Leg room - rear Shoulder room - front	14	- 60	1460		160		60	1460	1460	1460	1460	1460		460	1460	1460	1460	1460	1460	1460		
Head room - front	10		1020		20		20	1020	1020	1020	1020	1020		20	1020	1020	1020	1020	1020	1020		
Rear cargo space	10	-	730	10	-	10	-	1020	1020	730	730	1020	10	-	1020	1020	1020	1020	1020	1020		
9 1			700							700	700											
Mass (kg)	0000	0000			0000		0000	0000	0.100	0400	0400	0400	0400	0400	0400	0400	0400	0400	0.400	0400		
Gross Vehicle Mass (GVM)	3000	3000	3000	3000 3000		3000	3000	3000	3100	3100	3100	3100	3100	3100	3100	3100	3100	3100	3100	3100		
Kerb weight [^]		1695/1700	1770	1745 1825		1865	1950	2025	1780/1790	1855	2065	1900/1910	1950	2035	1905	2030	1970	2110	2115	2175		
Payload ⁻ (cab chassis models: final mass depends on body fitted) Gross Combination Mass (GCM)	1405/1380	1305/1300	1230 5850			1135 5500	1050 5850	975 5850	1320/1310	1245 6000	1035 6000	1200/1190 6000	1150 5500	1065 6000	1195 6000	1070 6000	1130 6000	990 6000	985	925 6000		
	5300/5500 2800/3000	5850 3500	3500	3000			3500	3500	3500	3500	3500	3500	3000	3500	3500	3500	3500	3500	6000 3500	3500		
Maximum towing mass (braked trailer) Maximum towing mass (non-braked trailer)	750	750	750	750	3500 750	3000 750	750	750	750	750	750	750	750	750	750	750	750	750	750	750		
Maximum towing mass (non-braked trailer) Maximum tow ball download (when fitted with genuine Isuzu UTE tow kit)	280/300	350	350	300	350	300	350	350	350	350	350	350	300	350	350	350	350	350	350	350		
Fuel tank capacity (litres)	76	76	76	76	76	76	76	76	76	76	76	76	76	76	76	76	76	76	76	76		
Tuel talik capacity (littes)	70	70	70	70	70	70	70	70	70	70	70	70	70	70	70	/0	70	70	/0	70		

^AFuel consumption & emissions figures based on ADR 81/02 & are to be used for vehicle comparison purposes only. Actual fuel consumption & emissions will vary depending on many factors including, but not limited to, traffic conditions, individual driving style & vehicle condition. [^]Kerb weight - unladen mass of vehicle & full tank of fuel, excludes tray body for cab chassis vehicles. Fuel weight ratio is based on Fuel Standard (Automotive Diesel) Determination 2001.

[^]Payload equals GVM minus kerb weight. *Limited stock available on these models. Please contact your local Isuzu UTE Dealer for more information.

CAB CHASSIS BODY STYLES AND DIMENSIONS (23MY)



SX Single Cab Chassis 4x2 & 4x4




SX Space Cab Chassis 4x2 & 4x4




SX Crew Cab Chassis 4x2 & 4x4




LS-M Crew Cab Chassis 4x4













































CAB CHASSIS AND UTE BODY STYLES AND DIMENSIONS (23MY)




LS-U Crew Cab Chassis 4x4













SX Crew Cab Ute 4x2 & 4x4














LS-M Crew Cab Ute 4x4











UTE BODY STYLES AND DIMENSIONS (23MY)




LS-U Space Cab Ute 4x4














LS-U Crew Cab Ute 4x2 & 4x4 LS-U+ Crew Cab Ute 4x4














X-TERRAIN Crew Cab Ute 4x4









COLOURS AND TRIM (23MY)

Body Colours



Basalt Black mica



Mercury Silver metallic



Mineral White



Neptune Blue mica



Obsidian Grey mica



Moonstone White pearl
(LS-U Range & X-TERRAIN Exclusive)



Magnetic Red mica
(LS-U Range & X-TERRAIN Exclusive)



Granite Grey mica (X-TERRAIN Exclusive)



Volcanic Amber metallic (X-TERRAIN Exclusive)

Interior Trim



Standard Black Cloth (On SX models)

High Grade Cloth (On LS-M & LS-U models)

Leather Accented[†] (On LS-U+)

Leather Accented' with Red Stitching (On X-TERRAIN)

TRAY STYLES

Economy Alloy



General Purpose Alloy



Heavy Duty Alloy



Heavy Duty Steel



Mine Specification Steel



Single































