23MY ISUZU MU-X SPECIFICATIONS

Engine

Series	Isuzu 4JJ3-TCX
Description	3.0 litre turbo-diesel, in-line 4-cylinder, DOHC, 16-valve with Diesel Particulate Diffuser (DPD)
Maximum torque	450Nm @ 1600→2600 rpm (automatic)
Maximum power	140kW @ 3600 rpm
Bore x stroke	95.4mm x 104.9mm
Displacement	2999сс
Compression ratio	16.3 : 1
Cylinder head	Isuzu-patent special aluminium alloy
Valve gear	Chain-driven dual overhead camshafts, roller rockers, 4 valves/cylinder
Induction	Electronic high pressure common rail direct fuel injection with VSS (Variable Swirl System) and intercooled electric control VGS (Variable Geometry System) turbocharger
Cylinder block	Cast iron upper with induction-hardened cylinder bores, cast alloy lower
Emission level	Euro 5
Alternator	120 amp with Intelligent Battery Sensor (IBS)

Transmissions

Automatic	Aisin AWR6B45 II 6-speed with sequential shift and brake shift lock electronically controlled, tri-mode with Adaptive Logic Control and fuel-saving lock-up torque converter on gears 3, 4, 5 and 6 • Uphill/Downhill Transmission Control: holds gear in varied-gradient ascents, selects gear on steep descents to hold speed with engine braking				
Ratios: 1	1st 2nd 3rd 4th 5th 6th Reverse	eed Automatic 3.600 2.090 1.488 1.000 0.687 0.580 3.732			
Final drive	4x2 4x4	3.727 3.727			
	Snorkelled diff breathers to increase fording depth and reduce mud blockage				
Transfer gearing	4x4 low-range 4x4 high-range	2.482 1.000			
4x4 system	"Rough Terrain Mode" and "Terrain Command" control with 'shift on the fly' 2-high ←→4-high selection at up to 100km/h, 4-low with rear differential lock				
Drivetrain system	TCS (Traction Control System) on all model variants				

Steering

Electric power steering with speed-sensing steering feel (light at low speed, heavy at high speed); tilt and telescopic adjustable steering wheel

Speed-sensitive variable capacity Electric power system; 3.84 turns lock-to-lock via tilt-adjustable steering wheel

Chassis

Ladder frame chassis constructed with high-tensile steel with 9 crossmembers

Front suspension

Independent, high-ride, coil springs, gas shock absorbers, upper and lower wishbones, stabiliser bar

Rear suspension

Multi-link coil suspension, gas shock absorbers, stabiliser bar

Axles

Front

Independent 4x4: fully floating with outer CV, inner double offset joints and equal length driveshafts. Rating: 1450kg

Rigid semi-floating banjo with hypoid final drive and dual tapered needle roller bearings. Rating: 1650kg

Brakes

Anti-lock Brake System (ABS) with Electronic Brakeforce Distribution (EBD), Electronic Stability Control (ESC). Emergency Brake Assist (EBA), Traction Control System (TCS), Roll Over Mitigation, Hill Start Assist (HSA), Hill Descent Control (HDC) and Trailer Sway Control (TSC)

All models: 320mm dia. ventilated front discs with 2-piston calipers, 318mm dia. ventilated rear discs with 1-piston calipers

Power-assisted via 10" servo unit; central electrical switch park brake

Wheels and Tyres

	4x4 & 4x2 LS-M	17" x 7" alloy; 255 / 65 R17 All-Terrain
	4x4 & 4x2 LS-U	18" x 7.5" alloy; 265 / 60 R18 Highway-Terrain
	4x4 & 4x2 LS-T	20" x 7.5" alloy; 265 / 50 R20 Highway-Terrain
	Spare	LS-M & LS-U Models: full size steel spare wheel LS-T Models: full size alloy spare wheel

Service Plus

Warranty	For the ultimate peace of mind, every Isuzu MU-X comes standard with a comprehensive, bumper-to-bumper 6 years/150,000km warranty^.
Roadside Assistance	Enjoy up to 7 years Roadside Assistance ^{<} when you complete your scheduled services at a Participating Isuzu UTE Dealer.
Capped Price Servicing	As an owner you will get access to our Capped Price Servicing ⁵ Program. The CPS Program covers the first 7 Scheduled Services in line with the Scheduled Service Intervals.

^6 years/150,000km (whichever occurs first), for Isuzu UTE Vehicles with a Warranty Start Date on or after 1/1/19. Excludes trays & accessories. The Roadside Assistance Program ("RSA Program") provides Coverage to RSA Eligible Vehicles (Private, ABN and Business Fleet Customers only) with a Warranty Start Date on or after 1/9/20 for a maximum of 7 years (unlimited kilometres). Initial 13 months Coverage provided from the Warranty Start Date. The Coverage will be reset for another 13 months from each date that a Participating Isuzu UTE Dealer conducts a Scheduled Service on the vehicle. For full terms & conditions visit isuzuute.com.au/roadside-assistancedisclaimer. The Capped Price Servicing Program ("CPS Program") applies to CPS Eligible Vehicles (excludes Rental & Government Customers) at Participating Isuzu UTE Dealers only. For 19MY & later vehicle models, the Capped Price Servicing covers the first 7 Scheduled Services for up to 7 years/105,000km (whichever occurs first). CPS Program is subject to change. For full terms & conditions, current pricing & model eligibility visit isuzuute.com.au/service-plus-disclaimer.









Safety

IDAS

Every MU-X comes with Isuzu's Intelligent Driver Assistance System (IDAS#) built-in to protect and enhance the driving experience. IDAS includes smart technologies as well as other passive and active safety features.

*IDAS features are designed to assist the driver, but should not be relied upon nor used as a substitute for safe driving practices. Feature operation may vary in different driving conditions. For full explanation of limitations, see Owner's & Driver's Manual.





The entire MU-X range has achieved a maximum 5-star ANČAP safety rating in 2020.







SPECIFICATIONS 4x2+ 4x4+ LS-U LS-T LS-M LS-T LS-M LS-U **Engine** 2999cc DOHC 4cyl. with intercooled turbocharger (450Nm, 140kW) **Transmissions** 6-speed "Rev-Tronic" automatic transmission with sequential sport mode **Safety and Security** 4-channel 4-sensor Anti-lock Brake System (ABS) with Electronic Brakeforce Distribution (EBD) Electronic Stability Control (ESC) Traction Control System (TCS) Emergency Brake Assist (EBA) Hill Start Assist (HSA) Hill Descent Control (HDC) Roll-Over Mitigation (ROM) Autonomous Emergency Braking (AEB) Turn Assist with AEB Post-Collision Braking (PCB) Forward Collision Warning (FCW) Misacceleration Mitigation Adaptive Cruise Control (ACC) with Stop and Go Functionality Traffic Sign Recognition (TSR) Intelligent Speed Limiter Manual Speed Limiter Lane Departure Warning (LDW) Lane Departure Prevention (LDP) Lane Keep Assist (LKA) Emergency Lane Keeping (ELK) Lane Support System (LSS) Switch (disables LDW, LDP, LKA, ELK) Driver Attention Assist Blind Spot Monitoring (BSM) Rear Cross Traffic Alert (RCTA) BSM/RCTA Auto Switch Off (disables BSM/RCTA when the genuine tow harness is connected) Reversing Camera with dynamic guidelines Front Park Assist Sensors Rear Park Assist Sensors 8 Airbags: dual front, curtain, side, driver's knee and far side airbags Passenger side SRS airbag on/off switch Height-adjustable upper mounts for front seat belts Pre-tensioners with load limiters for front seat belts Pre-tensioners with load limiters for outer second row seat belts 3-point retractable seat belts for third row and centre seating positions Intelligent seatbelt reminder (all seats) Three childseat top tethers for second row Two ISO FIX compatible anchor points for second row Height-adjustable head restraints for all seats Child-proof rear door locks Anti-theft alarm Side anti-intrusion bars inside all doors Engine immobilizer Rear window demister with timer and intermittent wiper High Density Polyethylene (HDPE) fuel tank High mount brake light on tailgate Dual horn **Protection** Under-front steel skid plate Steel plate guards: sump, transfer case, fuel tank leading edge; reinforced resin under fuel tank **Suspension and Brakes** Electric Park Brake with Auto Hold feature Single 10 inch servo brake master cylinder

Front independent, coil spring suspension w/gas shock absorbers, upper and lower wishbones and stabiliser bar Heavy-duty brakes: 320mm ventilated front discs w/twin-pot calipers, 318mm ventilated rear discs with single-pot calipers

Rear 5-link coil suspension with stabiliser bar

^{*}Limited stock available on these models. Please contact your local Isuzu UTE Dealer for more information.

SPECIFICATIONS 4x2+ 4x4+ LS-M LS-U LS-T LS-M LS-U LS-T Seating High grade cloth seats Leather accented seats Front bucket whiplash protection seats 6-way adjustable driver seat 8-way electric adjustable driver seat Electric adjustable lumbar support (driver seat only) 4-way electric adjustable front passenger seat 60:40 reclining split-fold second row seats with fold away centre arm rest 50:50 reclining split-fold third row seats Variable heated front driver and passenger seats **In-cabin Storage** Upper and lower glovebox compartments Power outlet in lower instrument panel Centre floor console with two USB ports Dual-purpose driver and front passenger cup holder tray Rear passenger door cup holders Second row fold out cup holder/storage tray Third row outer armrests with integrated cup holders Pockets on backs of front seats Overhead console with twin map lights and flip-down sunglasses case Front door storage compartment with bottle bulge Two coat hooks Flip up convenience hook behind passenger front seat Storage space under rear cargo flooring Tool storage space inside rear cargo wall (driver side) **Exterior Style** Short front overhang for optimal manoeuvrability and approach angle Bi-LED headlights with auto-levelling function Automatic headlights Automatic high beam Coming home light LED Daytime Running Lights (DRLs) LED fog lights Black and gunmetal grey grille Magnetite and black chrome grille Colour-coded front bumper Black aluminium side steps Magnetite aluminium side steps Black door handles Colour-coded door handles Manual tailgate with integrated rear spoiler Hands-free power tailgate with integrated rear spoiler Colour-coded power fold-in door mirrors with integrated turn indicators Black power door mirrors Rear privacy glass Heated door mirrors Centre front roof-mounted bee-sting aerial

Roof rails (maximum load capacity 100kg)

LED rear combination lamps

SPECIFICATIONS

ahin Amanisia	LS-M	LS-U	LS-T	LS-M	LS-U	LS-T
abin Amenities						
Dual zone climate control air-conditioning with integrated heater/demister		•	•		•	•
Manual air-conditioning with integrated heater/demister	•	_		•	_	
Second and third row air-conditioning vents with controls	•	•	•	•	•	•
Pollen and fine particle air filter	•	•	•	•	•	•
Ower windows with one-touch up/down driver's window with safety stop	•	•	•	•	•	•
Comfort turn signal	•	•	•	•	•	•
Central locking with keyless entry	•	•	•	•	•	•
Smart keyless entry		•	•		•	•
Walk away door lock		•	•		•	•
Welcome home light		•	•		•	•
Push button start	•	•	•	•	•	•
Remote engine start			•			•
Ambient door lighting			•			•
Centre console overhead guidelight			•			•
Power-adjustable door mirrors with turn indicator lights		•	•		•	•
Power-adjustable door mirrors	•			•		
speaker sound system	•			•		
speaker sound system		•	•		•	•
) inch touchscreen display with Apple CarPlay® and Android Auto™		•	•		•	•
7 inch touchscreen display with Apple CarPlay® and Android Auto™	•			•		
Built-in satellite navigation with MID turn-by-turn directions		•	•		•	•
wo rear centre console USB charging ports	•	•	•	•	•	•
ilt and telescopic adjustable steering wheel with electric power steering	•	•	•	•	•	•
Jrethane steering wheel with cruise, audio and voice recognition controls	•			•		
eather steering wheel with cruise, audio and voice recognition controls		•	•		•	•
mart MID with digital speedometer, safety information, fuel economy & range, odometer, trip information and service reminder	•	•	•	•	•	•
yre Pressure Monitoring System		•	•		•	•
lectro-luminescent gauges	•	•	•	•	•	•
Ferrain Command" 4x4 select dial				•	•	•
lear Differential Lock button				•	•	•
Rough Terrain Mode button				•	•	•
utomatic Windshield Wipers	•	•	•	•	•	•
ntuitive Flat Wiper Blade		•	•		•	•
fanual day/night interior rear view mirror	•			•		
uto-dimming rear view mirror		•	•		•	•
un visors with vanity mirrors (driver and passenger) and ticket retaining strap (driver)		•	•		•	•
un visors with vanity mirror (passenger) and ticket retaining strap (driver)	•			•		
ixed A-pillar assist-grips for driver and front passenger	•	•	•	•	•	•
ixed B-pillar assist-grips for rear passengers	•	•	•	•	•	
folding assist-grips for driver and front passenger		•	•	•	•	
olding assist-grips for rear passengers	•	•	•	•	•	
Carpet flooring		•	•	•	•	•
12 volt power outlets in lower instrument panel and rear cargo area						

4x2+

FUEL, WEIGHTS AND DIMENSIONS		4x2			4x4	
MIL V ADD 01/03/ Fuel Concumution Values	LS-M	LS-U	LS-T	LS-M	LS-U	LS-T
MU-X ADR 81/02 ^Δ Fuel Consumption Values						
Transmission (AT = Automatic)	AT	AT	AT	AT	AT	AT
FUEL CONSUMPTION (litres/100km)						
Combined	7.8	7.8	7.8	8.3	8.3	8.3
Urban	9.6	9.6	9.6	10.3	10.3	10.3
Extra Urban	6.8	6.8	6.8	7.2	7.2	7.2
CO ² (g/km)						
Combined	206	206	206	220	220	220
Urban	253	253	253	271	271	271
Extra Urban	179	179	179	190	190	190
Dimensions (mm unless stated otherwise)						
Wheelbase	2855	2855	2855	2855	2855	2855
Overall length	4850	4850	4850	4850	4850	4850
Overall width (excluding door mirrors)	1870	1870	1870	1870	1870	1870
Overall height	1815	1825	1825	1815	1825	1825
Front overhang	895	895	895	895	895	895
Rear overhang	1100	1100	1100	1100	1100	1100
Wheel track width	1570	1570	1570	1570	1570	1570
Ground clearance	230	235	235	230	235	235
Turning circle diameter between kerbs (metres)	11.4	11.4	11.4	11.4	11.4	11.4
Approach angle	28.6°	29.2°	29.2°	28.6°	29.2°	29.2°
Departure angle	27.6°	26.9°	26.4°	27.6°	26.9°	26.4°
Ramp-over angle	22.6°	23.1°	23.1°	22.6°	23.1°	23.1°
Wading depth [‡]	800	800	800	800	800	800
Interior (mm)						
Leg room - front	1075	1075	1075	1075	1075	1075
Leg room - 2nd row	915	915	915	915	915	915
Leg room - 3rd row	850	850	850	850	850	850
Shoulder room - front	1460	1460	1460	1460	1460	1460
Head room - front	1020	1020	1020	1020	1020	1020
Rear cargo space - 2nd & 3rd row flat	2138	2138	2138	2138	2138	2138
Rear cargo space - 3rd row flat	1119	1119	1119	1119	1119	1119
Rear cargo space - 3rd row up	311	311	311	311	311	311
Mass (kg)						
Gross Vehicle Mass (GVM)	2700	2700	2700	2800	2800	2800
Kerb weight [^]	2045	2060	2090	2135	2155	2180
Payload~	655	640	610	665	645	620
Gross Combination Mass (GCM)	5900	5900	5900	5900	5900	5900
Maximum towing mass (braked trailer)	3500	3500	3500	3500	3500	3500
Maximum towing mass (non-braked trailer)	750	750	750	750	750	750
Maximum tow ball download (when fitted with genuine Isuzu UTE tow kit)	350	350	350	350	350	350
Fuel tank capacity (litres)	80	80	80	80	80	80

^aFuel consumption & emissions figures based on ADR 81/02 and are to be used for vehicle comparison purposes only. Actual fuel consumption & emissions will vary depending on many factors including, but not limited to, traffic conditions, individual driving style & vehicle condition.


*Up to 800mm of wading depth on all MU-X models when travelling at a consistent speed of 7km/h. Water ingress may occur if speed is not maintained or if the vehicle is static in water above 350mm.

*Kerb weight - unladen mass of vehicle & full tank of fuel. Fuel weight ratio is based on Fuel Standard (Automotive Diesel) Determination 2001. *Payload equals GVM minus kerb weight.


BODY STYLES AND DIMENSIONS




Isuzu MU-X LS-M 4x2 and 4x4














Isuzu MU-X LS-U 4x2 and 4x4














Isuzu MU-X LS-T 4x2 and 4x4









BODY COLOUR OPTIONS

Body Colours



Basalt Black mica



Magnetic Red mica



Moonstone White pearl (LS-U & LS-T Exclusive)



Cobalt Blue mica



Mercury Silver metallic



Obsidian Grey mica



Galaxy Blue mica
(LS-U & LS-T Exclusive)



Mineral White

TRIMS AND WHEELS

Interior Trim



High Grade Cloth (On LS-M & LS-U models)

Leather Accented (On LS-T models)

Wheels



LS-M
17" Alloy Wheels with All-Terrain Tyres

LS-U 18" Tungsten Silver Alloy Wheels with Highway-Terrain Tyres

LS-T 20" Machined Two-tone Alloy Wheels with Highway-Terrain Tyres



 $^{^{\}dagger}\text{Seats}$ have leather touches or accents, but are not wholly leather.